



SPECIFICATIONS



TX423SMCR
Shower Spray W/ Sink Tap, Chrome



TX423SV1NN5
Shower Spray W/ Sink Tap, Black

TX423SV1NPIV
Shower Spray W/ Sink Tap, Pastel Ivory


TX423SV1NW
Shower Spray W/ Sink Tap, White

OPERATING CONDITIONS




1. Water supply pressure : 0.05 ~ 0.75 MPa.
2. Ensure that water supply is clean (No Sand, Dirt, Etc.)

ATTENTION

1. Don't use abrasive cleaners or solvents on faucets and fittings.
2. As the product model is constantly updated, the actual product may not look the same as it shown in the diagram, but the basic installation principles are the same.
3. Close the Stop valve for Shower if it is not in use.



INSTALLATION




MAINTENANCE


All Finishes : Clean the finish with mild soap and warm water. Wipe entire surface completely dry with clean soft cloth. Many cleaners may contain chemicals, such as ammonia, chlorine, toilet cleaner etc. which could adversely affect the finish and are not recommended for cleaning

TROUBLESHOOTING


PROBLEM	CHECK POINT	SOLUTION
Water leaks around the hose	1, 2	Tighten
Water leaks around the handle	3, 4	Tighten
Handle is loose	5, 6	Tighten



SPESIFIKASI



TX423SMCR
Shower Spray W/ Sink Tap, Chrome



TX423SV1NN5
Shower Spray W/ Sink Tap, Black

TX423SV1NPIV
Shower Spray W/ Sink Tap, Pastel Ivory


TX423SV1NW
Shower Spray W/ Sink Tap, White

KONDISI OPERASIONAL




1. Tekanan sumber air: 0.05 ~ 0.75 MPa.
2. Pastikan kondisi sumber air adalah bersih (tidak ada pasir, kotoran dan lain lain)

PERHATIAN

1. Jangan gunakan pembersih atau pelarut abrasif pada faucet dan fitting.
2. Karena model produk terus mengalami pembaharuan, aktual produk mungkin tidak sama dengan gambar, tapi prinsip dasar pemasangan adalah sama.
3. Tutup Stop valve untuk Shower jika tidak digunakan.



PEMASANGAN



PEMELIHARAAN

Seluruh lapisan : Bersihkan lapisan akhir dengan sabun lembut dan air hangat. Lap seluruh permukaan hingga benar-benar kering dengan kain lembut yang bersih. Kebanyakan bahan pembersih mungkin mengandung bahan kimia, seperti amonia, klorin, pembersih toilet, dll. yang dapat mempengaruhi hasil akhir dan tidak disarankan untuk dibersihkan

PENYELESAIAN MASALAH

MASALAH	POIN PERIKSA	SOLUSI
Air bocor disekitar selang	1, 2	Kencangkan
Air bocor disekitar handle	3, 4	Kencangkan
Handle longgar	5, 6	Kencangkan

